

UNIQUE PATENTED LOCKABLE FEMALE C13 & C19 IEC CONNECTORS AND OUTLETS

Guards against accidental disconnection of Computers, PDU's, Servers and most Network Devices.



Suitable for use with 'ANY STANDARD' C14 or C20 inlet

- Protects appliances that are vulnerable to vibration
- Connector cannot be accidentally pulled or vibrated out of the inlet



Connectors and outlets can be used with standard IEC plugs and inlets.

But for extra protection use both to ensure against accidental removal of power cables connected to PDU's, Servers, Network devices etc.




NEW

THE ORIGINAL & PATENTED RETROFIT SOLUTION NOW COMES IN A REWIREABLE VERSION!

- Rewireable - offering total flexibility when assembling cables
- LSZH - Low Smoke Zero Halogen

WORLD'S FIRST
LOCKING REWIREABLE
C13 IEC CONNECTOR



Technical Information

FEMALE C13 & C19 IEC CONNECTORS AND OUTLETS

Cable Assemblies (Connector)

- IEC LOCK (C13/C19) to UK Plug
- IEC LOCK (C13/C19) to European Schuko Plug
- IEC LOCK (C13/C19) to (C14/C20) IEC Plug
- IEC LOCK (C13/C19) to NEMA 5-15P (USA) & Hospital Grade
- IEC LOCK (C13/C19) to Australian 3 Pin Plug
- IEC LOCK (C13/C19) to Swiss & Italian Plug
- IEC LOCK (C13) to Japanese Plug & Hospital Grade
- IEC LOCK (C13/C19) to Brazilian Plug
- IEC LOCK (C13/C19) to Stripped End
- IEC LOCK C13 to Chinese Plug

Cable Size (Connector)

C13: 3 x 1.00mm² H05VV-F / H05RN

C13: 3 x 18/16 AWG SVT / SJT

C13: 3 x 0.75/1.25mm² HVCTF

C13: 3 x 1mm² RVV

C19: 3 x 1.50mm² H05VV-F,

C19: 3 x 14/12 AWG SJT

Cable colours available: Black, Orange, Blue, Red & White

Test Information (Connector)

Test Body: KEMA, UL, SAA, KC, PSE, CCC

Test Standard: IEC/UL/AUS/NZS/K/EN 603201
PSE - Article 1 CNCA-C02-01

Cable Lengths (Connector)

300mm up to any length. Various cables lengths and assemblies are retained as stock items with further combinations being available for special order. Call our Sales Office for more information.

Patent Information (Connector)

EU No. EP1459412B1 **Int. No.** PCT/GB02/05714

Int. Pending Patent: GB/2013/00195 (IEC Lock+)

Design Patent EU: 002130054-0001 (IEC Lock+)

Design Patent China: 201230542097.0 (IEC Lock+)

Design patent USA: – D720,701 (IEC Lock+)

Approvals (Outlet)

10 A/250VAC: ENEC 05, KEMA KEUR

15 A/250VAC: UL

Patent (Outlet)

UK Number: 2463468B **EU Number:** EP2321879

HK Number: HK1141901

Chinese Patent No. 2009801353258

Standards (Outlet)

IEC/EN 60320-2-2/UL498

CSA C22.2 No 182.3-M1987

LOCKING REWIREABLE C13 IEC CONNECTOR

Rating

10A Max / 250V~ (Europe/Australia)

15A Max / 250V~ (USA/Japan)

Test Information

Test Body: KEMA, UL, SAA, PSE

Test Standard:

KEMA-KEUR Certified: EN 60320-1

UL 60320-1 / CSA C22.2 No. 60320-1

AUS/NZS 60320-1

PSE / Article 1

Patents:

PCT Pending

Cable Size

3C x 0.75mm²

3C x 1.00mm²

3C x 1.25mm²

3C x 1.50mm² Max

3C x 14-18awg